



## ProVantage Fluting WB

### Benefits

- Lightweight recycled fluting grade produced by ECO7
- Substance range starts at 80 g/m<sup>2</sup>
- Made of 100% recycled fibre
- Optimum runnability and processing properties
- Fully compliant with VDW standards
- 100% recyclable for environmentally sound packaging

### End-uses

- **Industrial packaging:** Automotive industry, Consumer durables, Chemicals, Furniture
- **Luxury packaging:** Electronics
- **Heavy-duty packaging**



ISEGA	ISO 9001	ISO 14001	OHSAS 18001	FSC®	PEFC™
•	•	•	•	•	•

### Typical Values

Properties	Method	Unit of measure	Substance (g/m <sup>2</sup> )							
			80*	85*	90*	100*	120*	130*	135*	160
Moisture	ISO 287	%	8							
SCT <sub>CD</sub>	ISO 9895	kN/m	1.36	1.48	1.6	1.8	2.16	2.34	2.43	2.95
CMT <sub>30</sub>	ISO 7236	N	115	130	145	170	204	221	230	260
Tensile stiffness index <sub>MD</sub>		kNm/g	11							
Tensile stiffness index <sub>CD</sub>		kNm/g	3.8							
Gurley	ISO 5636-5	s	max. 120							



Issued from 01.01.2020,  
latest version available on  
[www.mondigroup.com](http://www.mondigroup.com)

Test conditions:  
Typical values after conditioning,  
measured at 50 ± 2% RH and 23 ± 1°C (ISO 187:1990)

\*ECO Premium Service, fast delivery option