



## ProVantage Fluting WB

### Benefits

- Lightweight recycled fluting grade produced by ECO7
- Substance range starts at 80 g/m<sup>2</sup>
- Made of 100% recycled fibre
- Optimum runnability and processing properties
- Fully compliant with VDW standards
- 100% recyclable for environmentally sound packaging

### End-uses

- **Industrial packaging:** Automotive industry, Consumer durables, Chemicals, Furniture
- **Luxury packaging:** Electronics
- **Heavy-duty packaging**



ISEGA	ISO 9001	ISO 14001	OHSAS 18001	FSC®	PEFC™
•	•	•	•	•	•

### Typical Values\*\*

Properties	Method	Unit of measure	Substance (lb/1000 ft <sup>2</sup> )							
			16.4*	17.4*	18.4*	20.5*	24.6*	26.6*	27.7*	32.8
Moisture	ISO 287	%	8							
SCT <sub>CD</sub>	ISO 9895	lbf/inch	7.8	8.5	9.1	10.3	12.3	13.4	13.9	16.8
CMT <sub>30</sub>	ISO 7236	lbf	25.9	29.2	32.6	38.2	45.9	49.7	51.7	58.5
Tensile stiffness index <sub>MD</sub>		kNm/g	11							
Tensile stiffness index <sub>CD</sub>		kNm/g	3.8							
Gurley	ISO 5636-5	s	max. 120							



Issued from 01.01.2020,  
latest version available on  
[www.mondigroup.com](http://www.mondigroup.com)

Test conditions:  
Typical values after conditioning,  
measured at 50 ± 2% RH and 23 ± 1°C (ISO 187:1990)

\*ECO Premium Service, fast delivery option  
\*\*computed, based on TDS in SI units