



## ProVantage Fluting WB

### Benefits

- Lightweight recycled fluting grade produced by ECO7
- Substance range starts at 80 g/m<sup>2</sup>
- Made of 100% recycled fibre
- Optimum runnability and processing properties
- Fully compliant with VDW standards
- 100% recyclable for environmentally sound packaging

### End-uses

- **Industrial packaging:** Automotive industry, Consumer durables, Chemicals, Furniture
- **Luxury packaging:** Electronics
- **Heavy-duty packaging**



ISO 9001	ISO 14001	OHSAS 18001	FSC® Recycled	ISO/IEC 27001
•	•	•	•	•

### Typical Values\*

Properties	Method	Unit of measure	Substances (lb/1000 ft <sup>2</sup> )						
			20.5	22.5	25.6	27.7	30.7	35.8	41.0
Moisture	ISO 287	%	7.4						
Bursting strength	ISO 2758	lbf/in <sup>2</sup>	29.9	32.1	34.1	35.5	38.6	41.5	43.8
SCT <sub>CD</sub>	ISO 9895	lbf/inch	9.5	10.2	11.1	12.0	13.4	14.9	16.2
Tensile stiffness index <sub>MD</sub>	-	kNm/g	10.2						
Tensile stiffness index <sub>CD</sub>	-	kNm/g	4.5						

	<p>Issued from 01.01.2020, latest version available on <a href="http://www.mondigroup.com">www.mondigroup.com</a></p>	<p><b>Test conditions:</b> Typical values after conditioning, measured at 50 ± 2% RH and 23 ± 1°C (ISO 187:1990)</p>
--	---	--

\*computed, based on TDS in SI units