



## ProVantage Fluting WB Frigo

### Benefits

- Resistant to humid conditions
- High cost efficiency

### End-uses

- Packaging in humid environments
- Cold chain packaging, e.g. agricultural products
- Fruit and vegetable industry



|          |           |             |               |               |
|----------|-----------|-------------|---------------|---------------|
| ISO 9001 | ISO 14001 | OHSAS 18001 | FSC® Recycled | ISO/IEC 27001 |
| •        | •         | •           | •             | •             |

### Typical Values

| Properties                            | Method   | Unit of measure  | Substance (g/m <sup>2</sup> ) |      |      |
|---------------------------------------|----------|------------------|-------------------------------|------|------|
|                                       |          |                  | 140                           | 150  | 175  |
| Moisture                              | ISO 287  | %                | 7.4                           |      |      |
| Bursting strength                     | ISO 2758 | kPa              | 310                           | 323  | 335  |
| SCT <sub>CD</sub>                     | ISO 9895 | kN/m             | 2.50                          | 2.65 | 2.90 |
| Tensile stiffness index <sub>MD</sub> |          | kNm/g            | 9.5                           |      |      |
| Tensile stiffness index <sub>CD</sub> |          | kNm/g            | 4.5                           |      |      |
| Cobb <sub>60</sub> (top)              | ISO 535  | g/m <sup>2</sup> | 35                            |      |      |
| Cobb <sub>60</sub> (bottom)           | ISO 535  | g/m <sup>2</sup> | 35                            |      |      |



Issued from 01.01.2020,  
latest version available on  
[www.mondigroup.com](http://www.mondigroup.com)

**Test conditions:**  
Typical values after conditioning,  
measured at 50 ± 2% RH and 23 ± 1°C  
(ISO 187:1990)