



ProVantage Fluting WB

Benefits

- Lightweight recycled fluting grade produced by ECO7
- Substance range starts at 80 g/m²
- Made of 100% recycled fibre
- Optimum runnability and processing properties
- Fully compliant with VDW standards
- 100% recyclable for environmentally sound packaging

End-uses

- **Industrial packaging:** Automotive industry, Consumer durables, Chemicals, Furniture
- **Luxury packaging:** Electronics
- **Heavy-duty packaging**



ISO 9001	ISO 14001	OHSAS 18001	FSC® Recycled	ISO/IEC 27001
•	•	•	•	•

Typical Values									
Properties	Method	Unit of measure	Substance (g/m ²)						
			100	110	125	135	150	175	200
Moisture	ISO 287	%	7.4						
Bursting strength	ISO 2758	kN/m	206	221	235	245	266	286	302
SCT _{CD}	ISO 9895	kPa	1.7	1.8	2.0	2.1	2.4	2.6	2.8
Tensile stiffness index _{MD}	-	kNm/g	10.2						
Tensile stiffness index _{CD}	-	kNm/g	4.5						

	<p>Issued from 01.01.2020, latest version available on www.mondigroup.com</p>	<p>Test conditions: Typical values after conditioning, measured at 50 ± 2% RH and 23 ± 1°C (ISO 187:1990)</p>
--	---	--