

ProVantage KraftTop Liner X



Benefits

- Optimal Kraftliner alternative
- Identical surface to brown KL- 100% virgin fibres on top ply
- Excellent strength
- Burst index: 4.0
- Optimum runnability and processing properties
- Cost efficient

End-uses

- **Food & beverage packaging:** Fruit & vegetable packaging, Agricultural produce
- **Industrial packaging:** Automotive industry
- **Heavy-duty packaging**



Food Contact	ISO 9001	ISO 14001	ISO 45001	FSC®	PEFC™
•	•	•	•	•	•

Typical Values

Properties	Method	Unit of measure	Substance (g/m ²)								
			100	110	125*	135*	160*	170*	180*	200	225
Moisture	ISO 287	%	7.8								
Bursting strength	ISO 2758	kPa	341	404	415	452	488	567	583	662	683
SCT _{CD}	ISO 9895	kN/m	1.80	2.00	2.20	2.50	2.80	3.20	3.30	3.60	3.90
Tensile stiffness index _{MD}		kNm/g	11								
Tensile stiffness index _{CD}		kNm/g	4.8								
Cobb _{60 (top)}	ISO 535	g/m ²	30								
Dennison test	TAPPI 459 om-08	No.	16								

	<p>Issued from 01.01.2021, latest version available on www.mondigroup.com</p>	<p>Test conditions: Typical values after conditioning, measured at 50 ± 2% RH and 23 ± 1°C (ISO 187 : 1990)</p>
--	---	--

*ECO Premium Service, fast delivery option

WWF's Environmental Paper Company Index: Mondi's constant high packaging score increased from 73.7% in 2013 to 85.7% in 2019.