

ProVantage Fluting WB Frigo



Benefits

- Resistant to humid conditions
- High cost efficiency

End-uses

- Packaging in humid environments
- Cold chain packaging, e.g. agricultural products
- Fruit and vegetable industry



ISO 9001	ISO 14001	ISO 45001	FSC® Recycled	ISO/IEC 27001
•	•	•	•	•

Typical Values

Properties	Method	Unit of measure	Substance (g/m ²)		
			140	150	175
Moisture	ISO 287	%	7.4		
Bursting strength	ISO 2758	kPa	310	323	335
SCT _{CD}	ISO 9895	kN/m	2.50	2.65	2.90
Tensile stiffness index _{MD}		kNm/g	9.5		
Tensile stiffness index _{CD}		kNm/g	4.5		
Cobb ₆₀ (top)	ISO 535	g/m ²	35		
Cobb ₆₀ (bottom)	ISO 535	g/m ²	35		



Issued from 01.01.2021,
latest version available on
www.mondigroup.com

Test conditions:
Typical values after conditioning,
measured at 50 ± 2% RH and 23 ± 1°C
(ISO 187:1990)

WWF's Environmental Paper Company Index: Mondi's constant high packaging score increased from 73.7% in 2013 to 85.7% in 2019.