

## ProVantage Fluting WB Frigo



### Benefits

- Resistant to humid conditions
- High cost efficiency

### End-uses

- Packaging in humid environments
- Cold chain packaging, e.g. agricultural products
- Fruit and vegetable industry



ISO 9001	ISO 14001	ISO 45001	FSC® Recycled	ISO/IEC 27001
•	•	•	•	•

### Typical Values\*

Properties	Method	Unit of measure	Substances (lb/1000 ft <sup>2</sup> )		
			28.7	30.7	35.8
Moisture	ISO 287	%	7.4		
Bursting strength	ISO 2758	lbf/in <sup>2</sup>	45.0	46.8	48.6
SCT <sub>CD</sub>	ISO 9895	lbf/inch	14.3	15.1	16.6
Tensile stiffness index <sub>MD</sub>		kNm/g	9.5		
Tensile stiffness index <sub>CD</sub>		kNm/g	4.5		
Cobb <sub>60</sub> (top)	ISO 535	g/m <sup>2</sup>	35		
Cobb <sub>60</sub> (bottom)	ISO 535	g/m <sup>2</sup>	35		



Issued from 01.01.2021,  
latest version available on  
[www.mondigroup.com](http://www.mondigroup.com)

**Test conditions:**  
Typical values after conditioning,  
measured at 50 ± 2% RH and 23 ± 1°C  
(ISO 187:1990)

\*computed, based on SI units

**WWF's Environmental Paper Company Index:** Mondi's constant high packaging score increased from 73.7% in 2013 to 85.7% in 2019.