

## ProVantage Fluting WB



### Benefits

- Lightweight recycled fluting grade produced on ECO7
- Substance range starts at 80 g/m<sup>2</sup>
- Made of 100% recycled fibre
- Optimum runnability and processing properties
- Fully compliant with VDW standards
- 100% recyclable for environmentally sound packaging

### End-uses

- **Industrial packaging:** Automotive industry, Consumer durables, Chemicals, Furniture
- **Luxury packaging:** Electronics
- **Heavy-duty packaging**



Food Contact	ISO 9001	ISO 14001	ISO 45001	FSC®	PEFC™
•	•	•	•	•	•

### Typical Values

Properties	Method	Unit of measure	Substance (g/m <sup>2</sup> )							
			80*	85	90*	100*	120*	130	135*	160
Moisture	ISO 287	%	8.0							
SCT <sub>CD</sub>	ISO 9895	kN/m	1.36	1.48	1.60	1.80	2.16	2.34	2.43	2.95
CMT <sub>30</sub>	ISO 7236	N	115	130	145	170	204	221	230	260
Tensile stiffness index <sub>MD</sub>		kNm/g	11.0							
Tensile stiffness index <sub>CD</sub>		kNm/g	3.8							
Gurley	ISO 5636-5	s	max. 120							



Issued from 01.01.2021,  
latest version available on  
[www.mondigroup.com](http://www.mondigroup.com)

**Test conditions:**  
Typical values after conditioning,  
measured at 50 ± 2% RH and 23 ± 1°C (ISO 187:1990)

\*ECO Premium Service, fast delivery option

**WWF's Environmental Paper Company Index:** Mondi's constant high packaging score increased from 73.7% in 2013 to 85.7% in 2019.