

ProVantage Fluting WB



Benefits

- Lightweight recycled fluting grade produced on ECO7
- Substance range starts at 80 g/m²
- Made of 100% recycled fibre
- Optimum runnability and processing properties
- Fully compliant with VDW standards
- 100% recyclable for environmentally sound packaging

End-uses

- **Industrial packaging:** Automotive industry, Consumer durables, Chemicals, Furniture
- **Luxury packaging:** Electronics
- **Heavy-duty packaging**



Food Contact	ISO 9001	ISO 14001	ISO 45001	FSC®	PEFC™
•	•	•	•	•	•

Typical Values**

Properties	Method	Unit of measure	Substance (lb/1000 ft ²)							
			16.4*	17.4	18.4*	20.5*	24.6*	26.6	27.7*	32.8
Moisture	ISO 287	%	8.0							
SCT _{CD}	ISO 9895	lbf/inch	7.8	8.5	9.1	10.3	12.3	13.4	13.9	16.8
CMT ₃₀	ISO 7236	lbf	25.9	29.2	32.6	38.2	45.9	49.7	51.7	58.5
Tensile stiffness index _{MD}		kNm/g	11.0							
Tensile stiffness index _{CD}		kNm/g	3.8							
Gurley	ISO 5636-5	s	max. 120							

	<p>Issued from 01.01.2021, latest version available on www.mondigroup.com</p>	<p>Test conditions: Typical values after conditioning, measured at 50 ± 2% RH and 23 ± 1°C (ISO 187:1990)</p>
---	---	--

*ECO Premium Service, fast delivery option
**computed, based on SI units

WWF's Environmental Paper Company Index: Mondi's constant high packaging score increased from 73.7% in 2013 to 85.7% in 2019.