

Technical Data Sheet



ProVantage Aquaflute

Benefits

- Outstanding short-term water resistance
- High resistance to compression
- Excellent box stability and stackability
- Designed for lightweight packaging
- Predominantly fresh fibre
- In line with Mondi's Sustainable Product criteria

End-uses

- Food and beverage packaging
 - Fruit and vegetable packaging
 - Cold chain packaging
 - High-humidity and extreme-climate storage
 - Agricultural produce
- Secondary packaging



Food Contact	ISO 9001	ISO 14001	ISO 45001	FSC®	PEFC™
•	•	•	•	•	•

Typical Values*

Properties	Method	Unit of measure	Substance (lb/1000 ft ²)									
			22.9	24.6	25.6	26.6	27.7	30.7	32.8	35.8	37.9	41.0
Moisture	Online	%	9.7									
SCT _{CD}	ISO 9895	lbf/inch	14.8	16.0	16.7	17.8	18.8	21.5	22.8	24.9	25.8	28.2
Tensile stiffness index _{MD}		kNm/g	11.5									
Tensile stiffness index _{CD}		kNm/g	5.1									
CMT ₃₀	ISO 7263	lbf	56.7	65.0	70.8	75.5	80.3	92.2	98.2	107.5	111.1	122.7
Cobb ₆₀	ISO 535	g/m ²	50									
Gurley	ISO 5636-5	s	200									



Issued from 01.02.2022,
latest version available on
www.mondigroup.com

Test conditions:
Typical values after conditioning,
measured at 50 ± 2% RH and 23 ± 1°C
(ISO 187:1990)

* computed based on SI units

WWF's Environmental Paper Company Index: Mondi's constant high packaging score increased from 73.7% in 2013 to 85.7% in 2019.