

ProVantage Smartwhite



Benefits

- **Outstanding SCT_{CD}** on white top kraftliner level
- White fresh fibre top layer meets the most demanding **printing** requirements
- For all applications that don't require 100% fresh fibre
- A substance range from 23.6–35.8 lb/1000 ft²

End-uses

- Shelf-ready packaging
- POS displays
- Trays
- Consumer durables
- E-commerce
- Customised packaging



Food Contact	ISO 9001	ISO 14001	ISO 22000	ISO 45001	FSC®	PEFC™
•	•	•	•	•	•	•

Typical Values*

Properties	Method	Unit of measure	Substance (lb/1000 ft ²)					
			20.5	23.6	25.6	27.7	32.8	35.8
Moisture (average)	On-line	%	7.8					
SCT _{CD}	ISO 9895	lbf/inch	12.7	14.6	15.9	17.1	18.4	20.2
Bursting strength	ISO 2758	lbf/in ²	45.0	51.8	54.4	58.7	67.3	73.7
Scott plybond	TAPPI 569	ft . lbs/in ²	0.14				0.13	
Cobb ₆₀ (top)	ISO 535	g/m ²	30					
Brightness (top)	ISO 2470	%	82					
Bendtsen roughness (top)	ISO 8791-2	ml/min	250				300	

	<p>Issued from 01.05.2022, latest version available on www.mondigroup.com</p>	<p>Test conditions: Typical values after conditioning, measured at 50 ± 2% RH and 23 ± 1°C (ISO 187:1990)</p>
--	---	--

* computed based on SI units

WWF's Environmental Paper Company Index: Mondi's constant high packaging score increased from 73.7% in 2013 to 85.7% in 2019.