

## ProVantage Smartwhite



### Benefits

- **Outstanding SCT<sub>CD</sub>** on white top kraftliner level
- White fresh fibre top layer meets the most demanding **printing** requirements
- For all applications that don't require 100% fresh fibre
- A substance range from 115-175 gsm

### End-uses

- Shelf-ready packaging
- POS displays
- Trays
- Consumer durables
- E-commerce
- Customised packaging



Food Contact	ISO 9001	ISO 14001	ISO 22000	ISO 45001	FSC®	PEFC™
•	•	•	•	•	•	•

### Typical Values

Properties	Method	Unit of measure	Substance (g/m <sup>2</sup> )					
			100	115	125	135	160	175
Moisture <small>(average)</small>	On-line	%	7.8					
SCT <sub>CD</sub>	ISO 9895	kN/m	2.22	2.55	2.78	3.00	3.23	3.54
Bursting strength	ISO 2758	kPa	310	357	375	405	464	508
Scott plybond	TAPPI 569	J/m <sup>2</sup>	300				280	
Cobb <sub>60</sub> <small>(top)</small>	ISO 535	g/m <sup>2</sup>	30					
Brightness <small>(top)</small>	ISO 2470	%	82					
Bendtsen roughness <small>(top)</small>	ISO 8791-2	ml/min	250				300	

	<p>Issued from 01.05.2022, latest version available on <a href="http://www.mondigroup.com">www.mondigroup.com</a></p>	<p><b>Test conditions:</b> Typical values after conditioning, measured at 50 ± 2% RH and 23 ± 1°C (ISO 187:1990)</p>
--	-------------------------------------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------

**WWF's Environmental Paper Company Index:** Mondi's constant high packaging score increased from 73.7% in 2013 to 85.7% in 2019.